

Three Phase Commit (3PC)

- Assumptions:
 - No network partitioning
 - At any point, at least one site must be up.
 - At most K sites (participants as well as coordinator) can fail
- Phase 1: Obtaining Preliminary Decision: Identical to 2PC Phase 1.
 - Every site is ready to commit if instructed to do so
- Phase 2 of 2PC is split into 2 phases, Phase 2 and Phase 3 of 3PC
 - In phase 2 coordinator makes a decision as in 2PC (called the pre-commit decision) and records it in multiple (at least K) sites
 - In phase 3, coordinator sends commit/abort message to all participating sites,
- Under 3PC, knowledge of pre-commit decision can be used to commit despite coordinator failure
 - Avoids blocking problem as long as < K sites fail
- Drawbacks:
 - higher overheads
 - assumptions may not be satisfied in practice



Three Phase Commit (3PC)

- Assumptions:
 - No network partitioning
 - At any point, at least one site must be up.
 - At most K sites (participants as well as coordinator) can fail
- Phase 1: Obtaining Preliminary Decision: Identical to 2PC Phase 1.
 - Every site is ready to commit if instructed to do so
 - Under 2 PC each site is obligated to wait for decision from coordinator
 - Under 3PC, knowledge of pre-commit decision can be used to commit despite coordinator failure.



3PC: Phase 2. Recording the Preliminary Decision

- Coordinator adds a decision record (<abort T> or < precommit T>) in its log and forces record to stable storage.
- Coordinator sends a message to each participant informing it of the decision
- Participant records decision in its log
- If abort decision reached then participant aborts locally
- If pre-commit decision reached then participant replies with <acknowledge T>



3PC: Phase 3. Recording Decision in the Database

- Executed only if decision in phase 2 was to precommit
- Coordinator collects acknowledgements. It sends < commit T> message to the participants as soon as it receives K acknowledgements.
- Coordinator adds the record < commit T> in its log and forces record to stable storage.
- Coordinator sends a message to each participant to <commit T>
- Participants take appropriate action locally



3PC: Handling Site Failure


- **Site Failure.** Upon recovery, a participating site examines its log and does the following:
 - Log contains < commit T> record: no action
 - Log contains <abort T> record: no action
 - Log contains <ready T> record, but no <abort T> or T> record: site consults Ci to determine the fate of T.
 - if Ci says T aborted, site executes undo (T) (and writes <abore T> record)
 - if Ci says T committed, site executes redo (T) (and writes < commit T> record)
 - ▶ if c says T committed, site resumes the protocol from receipt of precommit T message (thus recording precommit T> in the log, and sending acknowledge T message sent to coordinator).




3PC: Handling Site Failure (Cont.)

- Log contains commit T> record, but no <abort T> or <commit
 T>: site consults Ci to determine the fate of T.
 - if *Ci* says *T* aborted, site executes **undo** (*T*)
 - if Ci says T committed, site executes redo (T)
 - if Ci says T still in precommit state, site resumes protocol at this point
- Log contains no <**ready** *T*> record for a transaction *T*: site executes **undo** (*T*) writes <**abort** *T*> record



















site S_1


site S_2












 S_1

 S_2



coordinator



